

Appl. No. 10/613,932
Amdt. dated August 5, 2005
Reply to Office action of May 5, 2005

In the Claims:

Claims 1 and 4 are amended herein. The remaining claims are not amended in this response.

1. (currently amended) A numerical analysis system for performing numerical analysis by Finite Volume Method employing Hybrid Grid Adaptation Method, for analyzing physical quantities data of continuum medium, comprising:

(a) an initial grid memory containing an initial grid data including the physical measurement data made by way of free combination of tetrahedral cells, hexahedral cells and pentahedral cells;

(b) a grid dividing adapted means for dividing a cell into plural cells in order to divide a triangular face of a cell into plural triangular faces and divide a quadrilateral face of a cell into plural quadrilateral faces; and

(c) a grid deleting means recovering the former undivided cell by deleting divided cells,

said system thereby providing a modified grid data adapted for more efficient calculation and memory usage in analysis of said physical quantities data of said continuum medium.

2. (original) The numerical analysis system of claim 1, wherein said grid deleting means comprising:

Appl. No. 10/613,932
Amdt. dated August 5, 2005
Reply to Office action of May 5, 2005

(c1) a dividing threshold memory containing the dividing threshold;

(c2) a deleting threshold memory containing the deleting threshold;

(c3) a computing means to compute the divide-delete index depending upon the density in each cell;

(c4) a division deciding means deciding to divide the cell when the volume of the cell is greater than the minimum and when the division level of the cell is not maximal and when the divide-delete index is greater than the dividing threshold; and

(c5) a deletion deciding means deciding to delete the cell when the cell is not the initial cell of zero division level and when the divide-delete index is less than the deleting threshold.

3. (original) The numerical analysis system of claim 1, wherein said grid dividing means comprising:

(b1) a prism dividing means dividing a prismatic cell into 8 prismatic cells;

(b2) a hexahedron dividing means dividing a hexahedral cell into 8 hexahedral cells;

(b3) a pyramid dividing means dividing a pyramidal cell into 6 pyramidal cells and 4 tetrahedral cells;

(b4) a simple tetrahedron dividing means dividing a tetrahedral cell into 8 tetrahedral cells; and

Appl. No. 10/613,932
Amdt. dated August 5, 2005
Reply to Office action of May 5, 2005

(b5) a tetrahedron dividing means dividing a tetrahedral cell into 4 tetrahedral cells and 2 pyramidal cells.

4. (currently amended) A numerical analysis method processing numerical analysis by Finite Volume Method employing Hybrid Grid Adaptation Method, for analyzing grid data including physical quantities data of continuum medium, comprising:

(a) an initial FVM processing step to calculate the quantity including density of the continuum medium by Finite Volume Method depending upon the initial grid data made by using tetrahedral cells, hexahedral cells and pentahedral cells;

(b) an index processing step to calculate the divide-delete index of each cell depending upon the calculated density;

(c) a division processing step to divide a cell into plural cells in order to divide a triangular face into plural triangular faces and to divide a tetrahedral face into plural tetrahedral faces when the volume of the cell is greater than minimum and when the division level of the cell is not maximum and when the divide-delete index is greater than the division threshold;

(d) a deletion processing step to recover the undivided cell by deleting such cells that the cell is not the initial cell of zero dividing level and the divide-delete index is less than the deleting threshold;

(e) a renewal processing step to create the next grid;

Appl. No. 10/613,932
Amdt. dated August 5, 2005
Reply to Office action of May 5, 2005

(f) an FVM processing step to calculate the physical quantities including the density of the continuum medium by Finite Volume Method depending upon those grid data; and

(g) a repeating step to repeat those steps of (b) to (f),
thereby providing a modified grid data adapted for more efficient calculation and memory usage in analysis of said physical quantities data of said continuum medium.

5. (original) The numerical analysis method of claim 4, wherein a prismatic cell is divided into 8 prismatic cells, a hexahedral cell is divided into 8 hexahedral cells, a tetrahedral cell is divided into 6 pyramidal cells and 4 tetrahedral cells, a tetrahedral cell is divided into 8 tetrahedral cells or into 4 tetrahedral cells and 2 pyramidal cells.

6. (previously presented) The numerical analysis method of claim 4, wherein said continuum medium comprises a fluid.

7. (previously presented) The numerical analysis method of claim 4, wherein said data of continuum medium comprises a shock wave data of a fluid.

8. (previously presented) The numerical analysis method of claim 4, wherein said continuum medium comprises a compressible fluid.

Appl. No. 10/613,932
Amdt. dated August 5, 2005
Reply to Office action of May 5, 2005

9. (previously presented) The numerical analysis method of claim 4, wherein said data of continuum medium comprises a shock wave data of a compressible fluid.

10. (previously presented) The numerical analysis system of claim 1, wherein said continuum medium comprises a fluid.

11. (previously presented) The numerical analysis system of claim 1, wherein said continuum medium comprises a compressible fluid.

12. (previously presented) The numerical analysis system of claim 1, wherein said data of continuum medium comprises a shock wave data of a fluid.

13. (previously presented) The numerical analysis system of claim 1, wherein said data of continuum medium comprises a shock wave data of a compressible fluid.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.